



HighEnd Foto/Bildbearbeitung/Softproof/Vorstufe

Profi Foto/Design/Softproof

Foto/Softproof/Layout allgemein

OnPress Softproof

Modell	IP 262 ex	IP 240 ex LED	IP 242 ex	IP 220 ex	IP 242 LE	IP 220 LE	IP 213	IP 201	IP 190	PV 700
Größe	26"	24"	24"	22"	24"	22"	21.3"	20.1"	19"	21.3"
Auflösung	1.920 x 1.200	1.920 x 1.200	1.920 x 1.200	1.680 x 1.050	1.920 x 1.200	1.680 x 1.050	1.600 x 1.200	1.600 x 1.200	1.280 x 1.024	1.600 x 1.200
Paneltyp	S-IPS	S-IPS	S-IPS	S-IPS	S-PVA	S-PVA	S-IPS	S-IPS	S-IPS	IPS-Pro
Flächenabgleich	5x5	7x5 plus LED	5x5	5x5	3x3	3x3	---	---	-	passiv
Helligkeit (typ.)	400 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	400 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>	400 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>	270 cd/m <sup>2</sup>	700 cd/m <sup>2</sup>
Kontrast (typ.)	1.000:1	1.000:1	1000:1	1.000:1	1000:1	1000:1	550:1	800:1	700:1	1.000:1
Blickwinkel (typ.)	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V
Gamut (NTSC CIE31)	ca. 102%	ca. 110%	ca. 102%	ca. 92%	ca. 92%	ca. 92%	ca. 72%	ca. 72%	ca. 72%	ca. 72%
Gamut (ISOcoated v2)	max. 100%	max. 100%	max. 100%	max. 100%	max. 100%	max. 100%	max. 93%	max. 93%	max. 93%	max. 93%
Gamut (Adobe-RGB)	max. 100%	max. 100%	max. 100%	max. 96%	max. 93%	max. 93%	max. 78%	max. 78%	max. 78%	max. 78%
Farbtiefe	30 bit	30 bit nativ	30 bit nativ	30bit	30 bit	30 bit	30bit	30 bit	30 bit	30 bit
Kalibration	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware
Kalibrationsart	USB	USB	USB	USB	USB & DDC/ci	USB & DDC/ci	USB	USB	USB	USB
Präzision	48 bit	48 bit	48 bit	42 bit	36 bit	36 bit	30bit	30 bit	30 bit	36 bit
USB-Hub / Ports	USB 2.0 / 2	USB 2.0 / 2	USB 2.0 / 2	USB 2.0 / 2	USB 2.0 / 2	USB 2.0 / 2	USB 1.1 / 2	---	---	USB 2.0 / 2
Garantie*	60 Monate	60 Monate	60 Monate	60 Monate	36 Monate	36 Monate	60 Monate	60 Monate	60 Monate	36 Monate
Pixelfehler	● ————— max. 2 - kein Pixelfehler im Zentrum ————— ●			● ————— max. 3 ————— ●	● ————— max. 2 - kein Pixelfehler im Zentrum ————— ●			● ————— ISO 13406-2 ————— ●		
Erweiterter Modus	ja	ja	ja	ja	nein	nein	ja	ja	ja	ja
Referenz Modus	ja	ja	ja	ja	ja	ja	ja	ja	ja	ja
UDACT	ja	ja	ja	ja	nein	nein	ja	ja	ja	ja
Site-Lizenz	ja	ja	ja	ja	nein	nein	ja	ja	ja	ja
Lichtschutzblende	ja	ja	ja	ja	ja	ja	ja	ja	ja	ja

\*inklusive Panel und Backlight - ohne Alterung